



## Rocker switches



### B4 Series

**Square cut out - 30X22**  
**ENEC electrical rating up to 16A**






- Illuminated or not
- Rating up to 25 A / 125 V and 3/4 HP 125 V special version available
- IP protection degree increased by B4PRT
- Applications: ironing systems, hobby and work

*Customising on demand*

**Products**

**Accessories**


## Electrical features

ENEC electrical rating up to	<b>16A</b>
Electro-mechanical cycles number up to	<b>50.000</b>
Room temperature up to	<b>120 °C</b>
Flammability	<b>UL 94 V2</b>
Heat and fire resistance	<b>GWFI 850 °C</b> <b>GWIT 750 °C on demand</b>
Contact gap	<b>≥ 3 mm</b>
Approvals available (to check according to the rating of each single material code)	    
Reference standards	<b>EN 61058</b> <b>UL 1054</b>

## Wiring diagrams

- Double-pole intermediate switch
- Double-pole intermediate switch 2 momentary positions
- Double-pole momentary switch
- Double-pole switch
- Double-pole two-way switch
- Illuminated double-pole switch
- Illuminated double-pole switch independent light
- Illuminated double-pole two way switch
- Single-pole intermediate switch
- Single-pole switch

## Cut out (mm)



Z	Y	X
0.75 ... 1.25	22.0 <sup>+0.2</sup> <sub>0</sub>	30.0 <sup>0</sup> <sub>-0.1</sub>
1.25 ... 2.0	22.0 <sup>+0.2</sup> <sub>0</sub>	30.2 <sup>0</sup> <sub>-0.1</sub>
2.0 ... 3.0	22.0 <sup>+0.2</sup> <sub>0</sub>	30.6 <sup>0</sup> <sub>-0.2</sub>
3.0 ... 4.0	22.0 <sup>+0.2</sup> <sub>0</sub>	30.8 <sup>0</sup> <sub>-0.2</sub>

Stampa scheda