



Flange	Polyamide PA6
Elastomeric plate:	EPDM conforms following automotive standards; VW 2.8.1 G50, DBL 5556.10; DBL 5556.20; DBL 5556.21; ozone resistant according DIN 53509, Stufe 0 (best level)
Sealing	TPE

Properties	
Technology	tool-free connection technology for cabling of machines and equipment
Application	for introduction of cables, hoses, pneumatic and hydraulic lines
Advantage	fast and simple installation, up to 10 times faster than with cable glands, space savings of over 50%
Mounting	Mounting in wall thickness from 1.5 to 2.0 mm usable on panel cut-outs Size 24 for industrial multipole connectors (e.g. Harting or Wieland), for plates with thicknesses greater than 2.0 mm the cable entry plate can be attached
Temperature range (°C)	-30 +100
Protection grade	66
Overall dimension	L = 147,5 mm, L1 = 59,5 mm H = 25,0 mm, H1 = 8,2 mm

Features

Number of openings of the cable entry plate for cable diameter:

Desc ription	1,5- 2,6	2,5- 5,0	3,0- 5,5	3,0- 6,5	4,1- 8,1	5,0- 9,2	8,0- 12,0	8,0- 12,5	9,0- 14,0	9,6- 15,9	14,0- 20,0		Part No.
KAD P 24/11	-	-	-	4	-	4	-	-	-	-	3	1	F305-9240-00
KAD P 24/1 2	-	-	-	-	-	-	12	-	-	-	-	1	F305-9240-01
KAD P 24/1 3	-	-	2	-	6	-	-	-	4	-	1	1	F305-9240-02
KAD	-	-	-	6	-	4	-	-	-	4	-	1	F305-9240-03

Desc ription	1,5- 2,6	2,5- 5,0	3,0- 5,5	3,0- 6,5	4,1- 8,1	5,0- 9,2	8,0- 12,0	8,0- 12,5	9,0- 14,0	9,6- 15,9	14,0- 20,0		Part No.
P 24/1 4													
KAD P 24/1 7	-	-	-	-	-	17	-	-	-	-	-	1	F305-9240-04
KAD P 24/1 7-1	-	-	-	11	1	-	-	5	-	-	-	1	F305-9240-05
KAD P 24/2 2	-	-	-	16	-	4	-	2	-	-	-	1	F305-9240-06
KAD P 24/2 3	-	-	-	-	23	-	-	-	-	-	-	1	F305-9240-07
KAD P 24/2 9	-	-	-	29	-	-	-	-	-	-	-	1	F305-9240-08
KAD P 24/B LI	-	-	-	-	-	-	-	-	-	-	-	1	F305-9240-99