



## Characteristics

**Size:** 92 x 92 x 38mm (3.62" x 3.62" x 1.15")

**Construction:** Die-cast aluminum housing. Impeller is UL 94V-0 rating. Impedance protected. Lead wire or Terminal is available. Precise ball bearing or sleeve bearing system.

**Operating Temperature:**

Sleeve bearing -10°C to +70°C

Ball bearing -20°C to +80°C


**Insulation resistance:**

10 meg Ohms min. at 500V DC  
(between frame and terminal)

**Dielectric strength:**

1500 VAC one minute

**Weight:** 446 grams



Model No.	Bearing	Rated voltage(VAC)	Frequency (Hz)	Max.Rated current (mA)	Max.input power (W)	Speed (r.p.m.)	Max. Air Flow (CFM)	Max. Air Pressure (mmH2O)	Noise dB(A)
KLA115AP092ASWH	Sleeve	115	50/60	190/150	14/12	2750/3250	43/50	4.60/5.50	43/45
KLA115AP092ABWH	Ball	115	50/60	190/150	14/12	2750/3250	43/50	4.60/5.50	43/45
KLA230AP092ABWH	Sleeve	230	50/60	90/70	13/11	2750/3250	43/50	4.60/5.50	43/45
KLA230AP092AZWH	Ball	230	50/60	90/70	13/11	2750/3250	43/50	4.60/5.50	43/45