







FV71

**Screw-to-Tab
Terminal Block (3 poles)
with wire protector**



TECHNICAL DATA

	IEC Standards	American Standards
Ratings	450V - 25A	600V - 25A
Wire size	6.0 sqmm	22 ÷ 8AWG
Working Temperature	- 5 ÷ 150°C (short time 180°C)	23 ÷ 221°F
Plastic Material	Polyamide PA6.6 glass filled brown colour, UL94 V0, GWT 960°C	
Metal Parts	M4 zinc plated steel captive screw; 6.3 x 0.8 zinc plated steel tab insert; Wire protector made in brass; Other parts made in zinc plated steel	
Marking	L - N - 	

Approvals	File Nr.	Ratings (sqmm/AWG - V - A - T)	Standard References
	E 1937	6.0 sqmm - 450V - 25A - 150°C	EN 60998-1; EN60998-2-1; EN61210
	121086 ÜG	4.0 (flexible) / 6.0 (rigid) sqmm - 450V - - 25A (screw) / 15A (tab) - 150°C	DIN EN 60998-1; DIN EN 60998-2-1; DIN EN 61210 (VDE 0613)

PACKAGING

Type	P-N	Pack.	Dim. Pack. (LxHxP)	Weight (Kg)
FV 71 WP/3P	300589	750	40x20x40	13.0

DIMENSIONAL
DRAWING

