





>> FV71 wp

**Screw-to-Tab
Terminal Block (3 poles)
with wire protector**



Technical data

	IEC STANDARDS	AMERICAN STANDARDS
Ratings	450V - 25A	600V - 25A
Wire size	6.0 sqmm	22 ÷ 8 AWG (10.6 lb/in)
Working Temperature	- 5 ÷ 150°C (short time 180°C)	23 ÷ 221°F
Plastic Material	Polyamide glass fibre reinforced, UL94 VO, GWIT 775°C, GWFI 850°C	
Metal Parts	M4 (1.2Nm) zinc plated steel captive screw; 6.3 x 0.8 zinc plated steel tab insert; Wire protector made in brass; Other parts made in zinc plated steel	
Marking	L - N - 	

Approvals	File Nr.	Ratings (sqmm/AWG - V - A - T)	Standard References
	E1937	6.0 sqmm - 450V - 25A - 150°C	EN 60998-1; EN60998-2-1; EN61210
	40020946	4.0 sqmm (flexible) / 6.0 sqmm (rigid) - 450V - 25A - 150°C	EN 60998-1; EN 60998-2-1; EN 61210 (VDE 0613)

Dimensional drawing

I dati tecnici possono essere modificati senza preavviso. / The technical data can be subject to changes without notice.

