

Connettori paralleli preisolati Insulated parallel connectors

Rame elettrolitico stagnato e **PVC**
Temperatura di esercizio **T 105°C.**

*Electrolytic tinned copper and **PVC***
*Working temperature of **T 105°C.***

Approvazioni / Approvals




Codice Code	Sezione mm ² Section mm ²	L mm	B mm	C mm	Confezione Packing
5760000	1,5	16,0	8,0	1,7	100 o 1000 pz. / pcs.
5760300	2,5	16,0	8,0	2,3	100 o 1000 pz. / pcs.
5760600	6,0	20,5	8,5	3,4	100 o 500 pz. / pcs.

Connettori testa-testa preisolati Insulated butt connectors

Rame elettrolitico stagnato e **PVC**
Temperatura di esercizio **T 105°C.**

*Electrolytic tinned copper and **PVC***
*Working temperature of **T 105°C.***

Approvazioni / Approvals




Codice Code	Sezione mm ² Section mm ²	L mm	B mm	C mm	Confezione Packing
5765000	1,5	25,0	15,0	1,7	100 o 1000 pz. / pcs.
5765300	2,5	25,0	15,0	2,3	100 o 1000 pz. / pcs.
5765600	6,0	26,5	15,0	3,4	100 o 500 pz. / pcs.

Puntalini preisolati Insulated pin terminals

Rame elettrolitico stagnato e **PVC**
Temperatura di esercizio **T 105°C.**

*Electrolytic tinned copper and **PVC***
*Working temperature of **T 105°C.***

Approvazioni / Approvals




Codice Code	Sezione mm ² Section mm ²	W mm	L mm	F mm	B mm	D mm	C mm	Confezione Packing
5770000	1,5	1,9	19,0	9,0	10,0	3,4	1,7	100 o 1000 pz. / pcs.
5770300		1,9	22,0	12,0	10,0	3,4	1,7	100 o 1000 pz. / pcs.
5770600	2,5	1,9	19,0	9,0	10,0	4,1	2,3	100 o 1000 pz. / pcs.
5770900		1,9	22,0	12,0	10,0	4,1	2,3	100 o 1000 pz. / pcs.
5771200	6,0	2,8	27,0	13,0	13,0	5,6	3,4	100 o 500 pz. / pcs.

Puntalini preisolati piatti Insulated blade terminals

Rame elettrolitico stagnato e **PVC**
Temperatura di esercizio **T 105°C.**

*Electrolytic tinned copper and **PVC***
*Working temperature of **T 105°C.***

Approvazioni / Approvals



Codice Code	Sezione mm ² Section mm ²	W mm	L mm	F mm	B mm	D mm	C mm	Confezione Packing
5772000	1,5	3,0	21,5	11,0	10,5	3,4	1,7	100 o 1000 pz. / pcs.
5772300		3,0	24,5	14,0	10,0	3,4	1,7	100 o 1000 pz. / pcs.
5772600	2,5	2,8	19,0	9,0	10,0	4,1	2,3	100 o 1000 pz. / pcs.
5773200	6,0	2,8	22,5	10,0	12,5	5,6	3,4	100 o 500 pz. / pcs.